



LINDHAUS[®]
QUALITY CLEANING EQUIPMENT



PB 14e L-ion





RAISE YOUR EXPECTATIONS

The PB series was designed to give a professional solution for the specific requirements of the customer.

Lindhaus engineered this accessory like a machine, it is equipped with the most sophisticated technical features in the world.

Today, central vac systems, canister vacuums and Back pack vacuum cleaners without an electrified socket can be equipped with the PB14e L-ion battery power brush to increase efficiency in cleaning textile surfaces.

ENGINEERED TO LAST

Long service life and low vibration levels, are achieved with superior engineering and precision manufacturing. All rotating components are balanced and protected by electronic controls.

ELECTRONIC LOGIC

The electronic control is equipped with a soft start to avoid current peaks to the battery and motor, protects the motor and transmission from overload and assists the operator in adjusting the ideal height of the brush according to the type of carpet to be cleaned. If the roller gets stuck, it turns off the engine instantly. The rotation speed of 4000 RPM is kept constant as the load changes.

The central blue LED indicates the battery charge.

DESIGN SUPERIORITY

The sturdy and efficient battery power brush manages to vacuum everything that others leave behind. It requires no maintenance of the toothed belt, motor and electronics.

With non-marking rubber tires and an electrical switch position to stop the power brush motor, the transition to hard floor saves time and reduces airborne dust.

DRY CLEANING SYSTEM

The PB14e L-ion have the built in Lindhaus patented Dry Cleaning System; a perfect solution to clean and sanitize carpets and rugs with no risk and minimal effort. It scrubs the Lindhaus compound or crystal encapsulation system until it penetrates into the fibers reducing bacteria and dust mites. A short wait of 20 min. to let the carpet to dry and it can be sucked with the same power nozzle.

TECHNICAL DATA

PB 14e L-ion

Input power (W)	120
Electronic overload control	standard
Electric speed control	standard
Cogged drive belt	standard
Brush speed (RPM)	4000
Brush height adjustment	standard
Quick brush replacement no tools	standard
Dry Cleaning System	standard
Brush width mm (in)	350 (13.8)
Suction width mm (in)	380 (15)
Working time (min.)	> 60
Battery recharging time (min.)	120
Insulation class	III
Total weight included battery Kg (lb.)	3.3 (7.3)

HEADQUARTERS › LINDHAUS SRL

Via Belgio, 22 Z.I. 35127 › Padova, ITALY
tel. +39 049 8700307 › fax +39 049 8700605
vacuum@lindhaus.it › www.lindhaus.it

LINDHAUS USA

Minneapolis › Minnesota USA
info@lindhaus.com › www.lindhaususa.com

DISTRIBUTOR / DEALER